

Kod	İzolasyon kalınlığı (mm)	Yoğunluk (Kg/m ³)	Manşon Çapı (A) (mm)	Uzunluk (H) (mm)	Boyu (L) (mm)	Manşon Boyu (C) (mm)	Çap (B) (mm)
BSABM-R	50	50	100	300	410	55	200
BSABM-R	50	50	125	300	410	55	225
BSABM-R	50	50	100	600	710	55	200
BSABM-R	50	50	125	600	710	55	225
BSABM-R	50	50	160	600	710	55	260
BSABM-R	50	50	200	600	710	55	300
BSABM-R	50	50	250	600	710	55	350
BSABM-R	50	50	315	600	710	55	415
BSABM-R	50	50	400	600	710	55	500
BSABM-R	50	50	100	900	1010	55	200
BSABM-R	50	50	125	900	1010	55	225
BSABM-R	50	50	160	900	1010	55	260
BSABM-R	50	50	200	900	1010	55	300
BSABM-R	50	50	250	900	1010	55	350
BSABM-R	50	50	315	900	1010	55	415
BSABM-R	50	50	400	1200	1310	55	500
BSABM-R	50	50	315	1200	1310	55	415

Kod	Insulation Thickness (mm)	Volume (Kg/m ³)	Connection Plug Diameter (A) (mm)	Length (H) (mm)	Size (L) (mm)	Connection Plug Length (C) (mm)	Diameter (mm)
BSABM-R	50	50	100	300	410	55	200
BSABM-R	50	50	125	300	410	55	225
BSABM-R	50	50	100	600	710	55	200
BSABM-R	50	50	125	600	710	55	225
BSABM-R	50	50	160	600	710	55	260
BSABM-R	50	50	200	600	710	55	300
BSABM-R	50	50	250	600	710	55	350
BSABM-R	50	50	315	600	710	55	415
BSABM-R	50	50	400	600	710	55	500
BSABM-R	50	50	100	900	1010	55	200
BSABM-R	50	50	125	900	1010	55	225
BSABM-R	50	50	160	900	1010	55	260
BSABM-R	50	50	200	900	1010	55	300
BSABM-R	50	50	250	900	1010	55	350
BSABM-R	50	50	315	900	1010	55	415
BSABM-R	50	50	400	1200	1310	55	500
BSABM-R	50	50	315	1200	1310	55	415